

# Visualization Viewpoints

Editors: Theresa-Marie Rhyne and  
Lloyd Treinish

## Data Signatures and Visualization of Scientific Data Sets

Pak Chung  
Wong, Harlan  
Foote, Ruby  
Leung, Dan  
Adams, and Jim  
Thomas

Pacific  
Northwest  
National  
Laboratory

Today, as data sets used in computations grow in size and complexity, the technologies developed over the years to deal with scientific data sets have become less efficient and effective. Many frequently used operations, such as Eigenvector computation, could quickly exhaust our desktop workstations once the data size reaches certain limits.

On the other hand, the high-dimensional data sets we collect every day don't relieve the problem. Many conventional metric designs that build on quantitative or categorical data sets cannot be applied directly to heterogeneous data sets with multiple data types.

While building new machines with more resources might conquer the data size problems, the complexity of today's computations requires a new breed of projection techniques to support analysis of the data and verification of the results. We introduce the concept of a data signature, which captures the essence of a scientific data set in a compact format, and use it to conduct analysis as if using the original. A time-dependent climate simulation data set demonstrates our approach and presents the results.

### Background

In 1995, scientists at the Pacific Northwest National Laboratory (PNNL, on the Web at <http://www.pnl.gov>) had a challenging task: to analyze hundreds of thousands of unstructured text articles interactively on a desktop workstation. The solution—a system called Spire (Spatial Paradigm for Information Retrieval and Exploration)—has become one of the most powerful text analysis systems developed to date. (*R&D* magazine recognized it with an *R&D* 100 Award in 1996.) Among all the core technologies developed for this project, implementation of the document vectors, which represent individual topics of a corpus, plays a critical role in the system's success.

Because of the extremely compact design of the document vectors, many powerful—but potentially expensive—analysis techniques now can be applied to huge amounts of text data. Today we can interactively analyze more than half a million news articles, study their time trends, review topic correlation, and read the original text, all on a desktop workstation such as a Sun Ultra 10.

Figure 1 shows a visualization of a corpus with more than 60,000 medical research articles collected in 1997. We first project the corpus into individual document vec-

tors before generating the terrain visualization using scaling and other analysis techniques. Refer to an earlier article<sup>1</sup> or to <http://www.pnl.gov/infviz> on the Web for details of this visualization and the other interactive features the system provides.

### Data signature

Our research on information abstraction is neither static nor complete. The idea of document vectors has since evolved into the powerful concept of a data signature that represents the content within the context of scientific data sets. In scientific computations such as climate and combustion simulations and modeling, we encounter large data sets with up to tens of gigabytes of data recorded per time step. Many conventional analysis techniques are hopelessly ineffective when faced with this much data, and the development of new tools seemingly lags behind. The data signature concept represents one promising approach to analyzing and understanding scientific data sets.


A data signature can be described as a mathematical data vector that captures the essence of a large data set in a small fraction of its original size. It's designed to characterize a portion of a data set, such as an individual time-frame of a scientific simulation or an article within a corpus. These signatures enable us to conduct analysis at a higher level of abstraction and yet still reflect the intended results as if using the original data. For example, we can now measure the dissimilarity between two text articles by computing the difference between the two corresponding signatures and return a quantitative answer.

We have so far investigated designing data signatures for text, scalar fields, tensor fields, and a combination of these for data sets with multiple parameters. Our design is flexible enough to process both scalar and tensor fields, and project them into one numerical signature. The construction of a data signature is based on one or more of the following features and approaches:

- Velocity gradient tensors (Jacobians)
- Critical points and their Eigenvalues
- Orthogonal and nonorthogonal edges
- Covariance matrices
- Intensity histograms
- Content segmentation
- Conditional probability



**2** The color-coded terrain elevation overlaid with the wind-velocity field at the 850-mbar pressure level. The semi-opaque, centrally located isosurface represents the magnitude of the moisture advection. The particle-tracking icons depict the wind-velocity field.




between 18 and 26 May, the second between 2 and 16 June, and the last between 30 June and 13 July. Together, the three episodes of the unusually early and long rainy season clearly separate the summer into seven periods. These characteristics, however, don't show in Figure 2 because the simulation starts with a relatively calm day in the region.


We first project the water-vapor mixing ratio (scalar) and the wind-velocity (vector) variables of each time frame into a single data signature. We then create a symmetric matrix by measuring the similarities (or dissim-

ilarities) of the signatures representing individual time frames. Figure 3 depicts a 3D scatterplot generated by the three most significant principal components of the similarity matrix, P1, P2, and P3.

Each data signature (or its corresponding time frame) of the climate simulation is represented by a rainbow color icon in the 3D scatterplot, with the red icons showing the first period and the purple the last period. We selected the rainbow approach partly because we know a priori that the data set includes only seven distinctive time periods. Otherwise, an isoluminant, segmented

**3** The three axes represent the three most significant principal components of the similarity matrix. The seven time periods are shown in red (1 through 17), orange (18 through 26), yellow (27 through 32), green (33 through 47), cyan (48 through 60), blue (61 through 73), and purple (74 through 92).





4 An enhanced version of Figure 3 with a different camera viewpoint and extra lines connecting the colored spheres to show the ordering of the simulation.

color map would be ideal to depict the data. In the 3D scatterplot, as we can see, the simulation starts from the left (red and orange), across the middle (yellow, green, and cyan), and stops at the right (blue and purple).

Figure 4 shows an enhanced version of the scatterplot with a different camera viewpoint and extra lines connecting the colored spheres in the order they appeared in the simulation. Although the line icons create partial occlusions, they show the exact ordering of the simulation, which is missing in Figure 3.

The 3D scatterplot based on the water-vapor mixing ratio measurements and wind directions correctly reflects the trend, history, and similarity of characteristics from different time periods of the simulation. Interesting or unexpected characteristics of the simulation detected at this level will draw our attention to particular time intervals and physical interactions.

## Conclusions

Data signatures let us combine a multivariate scientific data set into a single quantitative data vector for scientific computation and analysis. Our design is flexible enough to unify different data types, including those to which it is seemingly difficult to apply any scale measures. The much smaller data signatures make good substitutes for their original large data sets in scientific computations such as climate modeling.

Our preliminary results indicate that this approach shows promise in simplifying the analysis and understanding of large data sets. It's still under active development, including addressing the problem of task-oriented feature selection. Therefore, we welcome ideas on extensions and improvements to our current methodology. ■

## Acknowledgments

The Pacific Northwest National Laboratory is managed for the US Department of Energy by Battelle Memorial Institute under contract DE-AC06-76R1-1830. Special thanks go to Lloyd Treinish and Theresa-Marie Rhyne, who provided valuable suggestions to improve our work. Thanks also to Ray Bair, Jackie Chen (Sandia National Laboratory [SNL]), Kris Cook, Dave Dixon, Thom Dunning, Sharon Eaton, George Fann, Habib Najm (SNL), Marty Peterson, Larry Rahn (SNL), and Paul Whitney, who provided assistance of many forms throughout this research.

## References

1. J. Wise et al., "Visualizing the Non-Visual: Spatial Analysis and Interaction with Information from Text Documents," *Proc. IEEE Information Visualization 95*, IEEE Computer Society Press, Los Alamitos, Calif., 1995, pp. 51-58.
2. L.R. Leung et al., "Intercomparison of Regional Climate Simulations of the 1991 Summer Monsoon in Eastern Asia," *J. of Geophysical Research*, Vol. 104, No. 6, Mar. 1999, pp. 6425-6454.
3. P.C. Wong and R.D. Bergeron, "Multivariate Visualization Using Metric Scaling," *Proc. IEEE Visualization 97*, ACM Press, New York, NY, 1997, pp. 111-118.

Readers may contact the authors by e-mail: pak.wong@pnl.gov, harlan.foote@pnl.gov, ruby.leung@pnl.gov, dan@pnl.gov, and jim.thomas@pnl.gov.

Contact department editors Rhyne and Treinish by e-mail at theresa.rhyne@epa.gov and lloyd@us.ibm.com.